



**Model
CA-2448-6MR
with Optional Drop-Gate**



Drop-Gate open



Drop-Gate removed

Removable Drop-Gate Truck

2000 lbs. Capacity

3-Sided bulk handling truck converts into a 4 sided box truck with the addition of a removable half "Drop-Gate" panel. Hinged in the center, it can easily be lowered to provide better access while loading or unloading, or raised and latched to secure contents for transport or storage. Expanded metal sides allow better visibility and airflow. Interior height 36" above deck. Available with and without drop gate panel. 2 swivel, 2 rigid, 6" x 2" mold-on rubber casters.

Size	TRUCK ONLY Model No.	Wt.	REMOVABLE DROP-GATE PANEL	Wt.	TRUCK WITH REMOVABLE DROP-GATE PANEL	Wt.
24 x 48	CA-2448-6MR	142	CA-RD48-PNL	26	CARD-2448-6MR	168
24 x 60	CA-2460-6MR	162	CA-RD60-PNL	31	CARD-2460-6MR	193
30 x 48	CA-3048-6MR	162	CA-RD48-PNL	26	CARD-3048-6MR	188
30 x 60	CA-3060-6MR	177	CA-RD60-PNL	31	CARD-3060-6MR	208

For 8" x 2" Mold-on Rubber Casters, use wheel code: **-8MR** (2400 lbs. Capacity)

For 8" x 2" Polyurethane Casters, use wheel code: **-8PY** (3600 lbs. Capacity)



**Model
CAWD-2448-6PY**

Welded Drop Gate Truck

3600 lbs. Capacity

Ideal for transporting or staging of bulkier materials. All models have a 12 gauge reinforced deck, and 2 swivel, 2 rigid 6" polyurethane casters with a pushbar handle on the swivel caster end. These all-welded units have a powder coated finish and ship fully assembled. Side panels are 13 gauge flattened expanded metal with 1-1/2" angle iron corners and top edge. Front drop-gate with spring latches provide easy access. Interior height - 36" above deck.

Size	Model No.	Wt.
24 x 48	CAWD-2448-6PY	160
24 x 60	CAWD-2460-6PY	185
30 x 48	CAWD-3048-6PY	180
30 x 60	CAWD-3060-6PY	200



3-Sided Bulk Trucks

Ideal for transporting or staging of bulkier materials. All models have a 12 gauge reinforced deck, and 2 swivel, 2 rigid casters with a pushbar handle on swivel caster end. All-welded units have a powder coated finish and ship fully assembled.

MESH SIDES

13 gauge flattened expanded metal with 1-1/2" angle iron corners and top trim. Available in two heights.

Deck Size D x W	Model No.	Wt.	Model No.	Wt.	
36" Interior Height		8" x 2" Mold-On Rubber 2400 lbs. Cap.		8" x 2" Polyurethane 3600 lbs. Cap.	
24 x 48	CA-2448-8MR	150	CA-2448-8PPY	140	
24 x 60	CA-2460-8MR	169	CA-2460-8PPY	159	
30 x 48	CA-3048-8MR	170	CA-3048-8PPY	160	
30 x 60	CA-3060-8MR	185	CA-3060-8PPY	175	
48" Interior Height		6" x 2" Mold-On Rubber 2000 lbs. Cap.		6" x 2" Polyurethane 3600 lbs. Cap.	
24 x 48	T1-2448-6MR	147	T1-2448-6PY	139	
24 x 60	T1-2460-6MR	163	T1-2460-6PY	155	
30 x 48	T1-3048-6MR	165	T1-3048-6PY	157	
30 x 60	T1-3060-6MR	182	T1-3060-6PY	174	



Mesh Sides

TUBULAR STEEL SIDES

48" interior height, 1.05" O.D. x 14 gauge round steel tubing.

Deck Size D x W	Model No.	Wt.	Model No.	Wt.	
		6" x 2" Mold-On Rubber 2000 lbs. Cap.		6" x 2" Polyurethane 3600 lbs. Cap.	
24 x 36	OT-2436-6MR	118	OT-2436-6PPY	108	
24 x 48	OT-2448-6MR	136	OT-2448-6PPY	126	
24 x 60	OT-2460-6MR	153	OT-2460-6PPY	143	
30 x 48	OT-3048-6MR	149	OT-3048-6PPY	139	
30 x 60	OT-3060-6MR	167	OT-3060-6PPY	157	



Tubular Sides

SLAT-TYPE SIDES

48" interior height, 1-1/2" x 3/16" slats.

Deck Size D x W	Model No.	Wt.	Model No.	Wt.	
		6" x 2" Mold-On Rubber 2000 lbs. Cap.		6" x 2" Polyurethane 3600 lbs. Cap.	
24 x 48	S1-2448-6MR	164	S1-2448-6PY	156	
24 x 60	S1-2460-6MR	182	S1-2460-6PY	174	
30 x 48	S1-3048-6MR	190	S1-3048-6PY	182	
30 x 60	S1-3060-6MR	216	S1-3060-6PY	208	



Slat-Type Sides

SOLID SIDES

48" interior height, 14 gauge solid steel with 1-1/2" angle iron corners and top edge.

Deck Size D x W	Model No.	Wt.	Model No.	Wt.	
		6" x 2" Mold-On Rubber 2000 lbs. Cap.		6" x 2" Polyurethane 3600 lbs. Cap.	
24 x 48	B1-2448-6MR	219	B1-2448-6PY	211	
24 x 60	B1-2460-6MR	244	B1-2460-6PY	236	
30 x 48	B1-3048-6MR	246	B1-3048-6PY	238	
30 x 60	B1-3060-6MR	273	B1-3060-6PY	265	



Solid Sides



Model
T3-3060-6PY
3 Shelf with Mesh Sides

3-Sided Shelf Trucks

Heavy 12 gauge shelves are enclosed on 3 sides, 48" high above the deck in sturdy 1-1/2" angle iron corners and top trim. Mesh sides and slat-type sides allow visibility and air circulation, while solid sides offer more durability. 2 swivel, 2 rigid 6" x 2" polyurethane casters with 3600 lbs. capacity. Overall height 57".

MESH SIDES - 13 gauge flattened expanded metal

SLAT-TYPE SIDES - 1-1/2" x 3/16" slats

SOLID SIDES - 14 gauge sheet steel

	SIZE W x L	2 SHELVES 22-1/2" Clearance Model No.	Wt.	3 SHELVES 15" Clearance Model No.	Wt.
Mesh Sides	24 x 48	T2-2448-6PY	173	T3-2448-6PY	219
	24 x 60	T2-2460-6PY	198	T3-2460-6PY	250
	30 x 48	T2-3048-6PY	200	T3-3048-6PY	251
	30 x 60	T2-3060-6PY	229	T3-3060-6PY	293
Slat Sides	24 x 48	S2-2448-6PY	198	S3-2448-6PY	234
	24 x 60	S2-2460-6PY	226	S3-2460-6PY	272
	30 x 48	S2-3048-6PY	233	S3-3048-6PY	274
	30 x 60	S2-3060-6PY	267	S3-3060-6PY	319
Solid Sides	24 x 48	B2-2448-6PY	253	B3-2448-6PY	295
	24 x 60	B2-2460-6PY	288	B3-2460-6PY	340
	30 x 48	B2-3048-6PY	290	B3-3048-6PY	342
	30 x 60	B2-3060-6PY	328	B3-3060-6PY	392

For 6" x 2" Mold-on Rubber Casters, use wheel code: **-6MR** (2000 lbs. Capacity)



Model
T3-2448-6PYFP60

Forkliftable Order Picking Truck

3600 lbs. Capacity

Large capacity, three shelf truck designed to securely attach to your order picker. Two full width fork pockets on 24" centers and 1-1/2" steel grab bar make attachment easy. Shelves have 19" clearance. Overall height is 69". 2 rigid and 2 swivel 6" polyurethane casters assure smooth rolling, even with a full load of 3600 lbs. 48" length allows the unit to fit down any aisle!

Size W x L	Model No.	Wt.
24 x 48	T3-2448-6PYFP60	258
30 x 48	T3-3048-6PYFP60	295



3-Sided Adjustable Shelf Trucks

3600 lbs. Capacity

Expanded metal on 3 sides extends 48" high above deck to help contain loads and improve visibility and airflow. Upper shelf is adjustable on 3-1/2" centers for versatility, and can be positioned with 1-1/2" lips either up or down. Shelves are 12 gauge steel. 3600 lbs. overall capacity with non-marking, long-lasting 6" x 2" polyurethane casters, 2 swivel, 2 rigid. Overall height is 57". Additional factory installed adjustable shelves are also available.

	DECK SIZE W x L	Model No.	Wt.
Mesh Sides	24 x 48	T2-A-2448-6PY	203
	24 x 60	T2-A-2460-6PY	228
	30 x 48	T2-A-3048-6PY	230
	30 x 60	T2-A-3060-6PY	259
Slat Sides	24 x 48	S2-A-2448-6PY	218
	24 x 60	S2-A-2460-6PY	256
	30 x 48	S2-A-3048-6PY	263
	30 x 60	S2-A-3060-6PY	297
Solid Sides	24 x 48	B2-A-2448-6PY	283
	24 x 60	B2-A-2460-6PY	318
	30 x 48	B2-A-3048-6PY	320
	30 x 60	B2-A-3060-6PY	358

For 6" x 2" Mold-on Rubber Casters, use wheel code: **-6MR**
(2000 lbs. Capacity)



Model T2-A-3060-6PY

Drop-Shelf Trucks

3600 lbs. Capacity

3-sided truck converts in seconds. Upper shelf drops down and out of the way to make room for extra large items, or it can be removed completely. Sides extend 48" above deck, with drop-shelf positioned 30" above deck. Rolls easily on 6" x 2" non-marking polyurethane casters, 2 swivel and 2 rigid. 3600 lbs. capacity.

MESH SIDES - 13 gauge flattened expanded metal

SLAT-TYPE SIDES - 1-1/2" x 3/16" slats

SOLID SIDES - 14 gauge solid steel

	DECK SIZE W x L	SHELF SIZE W x L	Model No.	Wt.
Mesh Sides	24 x 48	21 x 44	T1-2448-6PY-DS	181
	24 x 60	21 x 56	T1-2460-6PY-DS	206
	30 x 48	27 x 44	T1-3048-6PY-DS	209
	30 x 60	27 x 56	T1-3060-6PY-DS	237
Slat Sides	24 x 48	21 x 44	S1-2448-6PY-DS	198
	24 x 60	21 x 56	S1-2460-6PY-DS	225
	30 x 48	27 x 44	S1-3048-6PY-DS	234
	30 x 60	27 x 56	S1-3060-6PY-DS	271
Solid Sides	24 x 48	21 x 44	B1-2448-6PY-DS	253
	24 x 60	21 x 56	B1-2460-6PY-DS	287
	30 x 48	27 x 44	B1-3048-6PY-DS	290
	30 x 60	27 x 56	B1-3060-6PY-DS	328

For 6" x 2" Mold-on Rubber Casters, use wheel code: **-6MR**
(2000 lbs. Capacity)



Model T1-3060-6PY-DS



Release slide bolts to drop upper shelf down and out of the way



Shelf in raised position



Model
DET4-2448-6PY

2-Sided Shelf Trucks

3600 lbs. Capacity

Expanded metal ends improve visibility, allow 2-way access to material. End panels extend 48" high above deck. All-welded construction with 12 gauge steel shelves. Available in 2, 3 or 4 shelf configurations. Non-marking, quiet 6" polyurethane wheels, 2 swivel 2 rigid. Overall height 57". Capacity 3600 lbs.

SHELF SIZE	2 SHELVES 22-1/2" Clearance Model No.	Wt.	3 SHELVES 15" Clearance Model No.	Wt.	4 SHELVES 12" Clearance Model No.	Wt.
24 x 48	DET2-2448-6PY	154	DET3-2448-6PY	196	DET4-2448-6PY	238
24 x 60	DET2-2460-6PY	175	DET3-2460-6PY	217	DET4-2460-6PY	269
30 x 48	DET2-3048-6PY	178	DET3-3048-6PY	229	DET4-3048-6PY	281
30 x 60	DET2-3060-6PY	204	DET3-3060-6PY	268	DET4-3060-6PY	332

For 6" x 2" Mold-on Rubber Casters, use wheel code: **-6MR** (2000 lbs. Capacity)



Model
DET2-A-2448-6PY

2-Sided Adjustable Shelf Truck

3600 lbs. Capacity

Expanded metal ends extend 48" high above the deck, improve visibility, and allow 2-way access to material. All-welded construction with 12 gauge steel shelves. Standard truck has one upper shelf that is adjustable on 3-1/2" centers, and can be positioned with 1-1/2" lips either up or down. Additional adjustable shelves also available. 2 swivel and 2 rigid casters with quiet, non-marking 6" polyurethane wheels. Overall height 57". Capacity 3600 lbs.

Size W x D	Model No.	Wt.	Additional Shelf Model No.	Wt.
24 x 48	DET2-A-2448-6PY	184	SHLF-2447	43
24 x 60	DET2-A-2460-6PY	205	SHLF-2459	53
30 x 48	DET2-A-3048-6PY	208	SHLF-3047	53
30 x 60	DET2-A-3060-6PY	234	SHLF-3059	65

For 6" x 2" Mold-on Rubber Casters, use wheel code: **-6MR** (2000 lbs. Capacity)



Model
PPT-2848-6M

Pick-Pack Truck

with sloped shelves and divider

1600 lbs. Capacity

Upper shelves are sloped, bottom shelf has 1-1/2" retaining lip. 14 gauge shelves have 14" shelf clearance. Diamond caster pattern with 6" x 2" Mold-On rubber casters, 1600 lbs. capacity.

Size	Model No.	Shelf Size	Wt.
28 x 48	PPT-2848-6M	14 x 48	225
28 x 60	PPT-2860-6M	14 x 60	255



High End Truck with Removable Shelf

2000 lbs. Capacity

Narrow 16" wide 12 gauge steel deck is perfect for narrow aisles. Each corner has 5" polyurethane swivel wheels. Two 8" center wheels allow the unit to pivot within its own radius. All wheels are non-marking polyurethane. Two removable handles extend 48" above the deck to contain taller loads. The shelf can be mounted in three different heights (7-1/2", 21-1/2", 35-1/2" from the deck) on the upright cross braces. Shelf capacity 200 lbs.

Size	Model No.	Wt.
16 x 48	HE-1648-RS	127
16 x 60	HE-1660-RS	142



Model HE-1660-RS

High End 6-Wheeled Shelf Truck

2000 lbs. Capacity

Narrow width is ideal for busy aisles and two shelves create twice the loading area! 12 gauge shelves have 24" clearance. Six wheel design is fully maneuverable with two 8" x 2" rigid center wheels and four 5" swivel corner wheels. Non-marking polyurethane tread prevents wheel marks on your floor. End panels extend 48" high for extra capacity and are constructed from 1-1/2" x 3/16" slats for extra visibility. Capacity 2000 lbs.

Size	Model No.	Wt.
16 x 48	HE2-1648	118
16 x 60	HE2-1660	129
16 x 72	HE2-1672	152
24 x 48	HE2-2448	152
24 x 60	HE2-2460	190



Model HE2-2460

Narrow Aisle Order Picking Truck

2000 lbs. Capacity

Six wheel design creates a versatile two shelf truck that is perfect for use in warehouses and distribution centers where you need large capacity and zero turn maneuverability. The large writing shelf, measuring 21" wide and 12" deep, and storage pocket provide the work surface needed to fill out paperwork while picking orders. Constructed from 12 gauge steel and 1-1/2" angle, this workhorse is built to withstand the rigors of the most demanding facilities. The bottom shelf has 24" clearance and the end panels extend 48" above the deck. 8" rigid and 5" swivel non-marking polyurethane casters provide a smooth ride.

Size	Model No.	Wt.
24 x 48	HE2-2448-WSP	172
24 x 60	HE2-2460-WSP	210



Model HE2-2460-WSP



3-Sided Model
RP3S-2436-5PY



4-Sided Model
RP4X-1832-5PY

Raised Platform Box Trucks

Raised 12 gauge steel platform is 20" high to help minimize bending. Sides extend 20" high above the deck to help contain those big loads and small parts. All-welded construction ships fully assembled and ready for immediate use. 2 swivel, 2 rigid casters with non-marking polyurethane wheels.

1200 lbs. Capacity – 5" ball bearing wheels

2000 lbs. Capacity – 6" roller bearing wheels

SOLID SIDES

14 gauge steel sides.

Platform Size	Capacity	3-SIDED MODEL		4-SIDED MODEL	
		Model	Wt.	Model	Wt.
18 x 32	1200 lbs.	RP3S-1832-5PY	94	RP4S-1832-5PY	109
24 x 36	1200 lbs.	RP3S-2436-5PY	114	RP4S-2436-5PY	133
24 x 48	1200 lbs.	RP3S-2448-5PY	134	RP4S-2448-5PY	154
24 x 36	2000 lbs.	RP3S-2436-6PY	124	RP4S-2436-6PY	143
24 x 48	2000 lbs.	RP3S-2448-6PY	134	RP4S-2448-6PY	154
30 x 48	2000 lbs.	RP3S-3048-6PY	175	RP4S-3048-6PY	195
30 x 60	2000 lbs.	RP3S-3060-6PY	198	RP4S-3060-6PY	224

EXPANDED METAL SIDES

3/4" expanded metal sides for greater visibility and airflow.

Platform Size	Capacity	3-SIDED MODEL		4-SIDED MODEL	
		Model	Wt.	Model	Wt.
18 x 32	1200 lbs.	RP3X-1832-5PY	73	RP4X-1832-5PY	78
24 x 36	1200 lbs.	RP3X-2436-5PY	93	RP4X-2436-5PY	100
24 x 48	1200 lbs.	RP3X-2448-5PY	120	RP4X-2448-5PY	128
24 x 36	2000 lbs.	RP3X-2436-6PY	102	RP4X-2436-6PY	110
24 x 48	2000 lbs.	RP3X-2448-6PY	124	RP4X-2448-6PY	132
30 x 48	2000 lbs.	RP3X-3048-6PY	156	RP4X-3048-6PY	165

Raised Platform Trucks with Drop-Gate

Hinged Drop-Gate provides easier access when loading and unloading. Spring latches secure gate in upright position to retain load. Raised 12 gauge platform is 20" high to minimize bending, and sides extend 20" above platform. 2000 lbs. capacity with 6" x 2" polyurethane casters, 2 swivel and 2 rigid.

SOLID SIDES

14 gauge steel sides.

Platform Size	Model No.	Wt.
24 x 36	RPDS-2436-6PY	143
24 x 48	RPDS-2448-6PY	152
30 x 48	RPDS-3048-6PY	195

EXPANDED METAL SIDES

3/4" expanded metal for greater visibility and airflow.

Platform Size	Model No.	Wt.
24 x 36	RPDX-2436-6PY	110
24 x 48	RPDX-2448-6PY	124
30 x 48	RPDX-3048-6PY	156



Model
RPDS-2436-6PY



Model
RPDX-2436-6PY

Box Trucks

2000 lbs. Capacity

Bulk storage and transport trucks have 24" interior height. Overall height is 32" with 6" x 2" mold-on rubber casters, 2 swivel and 2 rigid.

SHEET STEEL TRUCKS

14 gauge steel sides in angle iron frame.

Deck Size	Model No.	Wt.
24 x 36	BTS2436-6MR	149
24 x 48	BTS2448-6MR	175
30 x 48	BTS3048-6MR	192
30 x 60	BTS3060-6MR	217



Model
BTS2436-6MR



Model
BTX2436-6MR

EXPANDED METAL TRUCKS

Angle iron frame with 3/4" expanded metal sides for greater visibility and airflow.

Deck Size	Model No.	Wt.
24 x 36	BTX2436-6MR	101
24 x 48	BTX2448-6MR	117
30 x 48	BTX3048-6MR	130
30 x 60	BTX3060-6MR	145

Box Trucks with Hinged Lid

2000 lbs. Capacity

Bulk storage and transport trucks have 24" interior height. Double-hinged top cover has padlock hasp for security. Overall height is 33-1/2" with 6" x 2" mold-on rubber casters, 2 swivel and 2 rigid. 2000 lbs. capacity.

SHEET STEEL TRUCKS

14 gauge steel sides in angle iron frame provides maximum durability.

Deck Size	Model No.	Wt.
24 x 36	BTSL2436-6MR	173
24 x 48	BTSL2448-6MR	206
30 x 48	BTSL3048-6MR	230
30 x 60	BTSL3060-6MR	264



Model
BTSL2436-6MR

EXPANDED METAL TRUCKS

Angle iron frame with 3/4" expanded metal sides for greater visibility and airflow.

Deck Size	Model No.	Wt.
24 x 36	BTXL2436-6MR	117
24 x 48	BTXL2448-6MR	139
30 x 48	BTXL3048-6MR	155
30 x 60	BTXL3060-6MR	174



Model
BTXL2436-6MR



Model
HT-4857-6PH

Low-Profile Hopper Truck – 12” Deep

2000 lbs. Capacity

All-welded construction. Angled “scoop” side allows for use under machinery. Designed to catch chips, cutoff, and scraps produced by metalworking. Two swivel, two rigid casters with 6” x 2” phenolic wheels allow for smoother rolling of heavy loads. Hopper height is 20”. Removable handle is 40” high. Powder coated finish.

Overall W x D x H*	Model No.	Wt.
48 x 59 x 20	HT-4857-6PH	206

* Includes handle pockets, but does not include handle dimensions.



Model
HT-3651-6PH

Low-Profile Hopper Truck – 16” Deep

2000 lbs. Capacity

All-welded construction. Angled “scoop” side allows for use under machinery. Designed to catch chips, cutoff, and scraps produced by metalworking. Hopper height is 24”. Removable handle is 40” high, and can be placed on either of the three sides. Four swivel casters with 6” x 2” phenolic wheels for maneuverability under equipment overhangs/under machinery. Powder coated finish.

Overall W x D x H*	Model No.	Wt.
54 x 38 x 24	HT-3651-6PH	183

* Includes handle pockets, but does not include handle dimensions.



Model
HT-2751-6PY

Hopper Truck

2000 lbs. Capacity

14 gauge, fully welded, leakproof construction. 3/4 cubic yard capacity. 2 rigid and 2 swivel casters with 6” polyurethane wheels provide a smooth rolling truck even when fully loaded. Top edge is reinforced with 1” angle for extra durability. 3/16” thick dumping knees offer two step dumping action. Two 1” diameter handles won’t cut into your operators’ hands when lifting. Heavy-duty gray powder coated finish.

Overall W x D x H	Model No.	Wt.
27 x 56-3/4 x 40-5/8	HT-2751-6PY	149

WELDED STEEL Mobile Storage Bins

Heavy-Duty, all-welded 12 gauge steel construction with powder coated finish for rugged durability. Built with an open hopper front, each level has overall dimensions of 12-1/2"H x 15"D x 32"W. Available with up to 4 permanent storage compartments per level. Heavy 6" x 2" swivel casters with hard tread phenolic wheels for ease of movement. Mobile units allow you to bring the parts to the workspace or reposition with changing requirements.

Overall Dimensions: 32" wide x 45-1/2" high x 20" deep. 800 lbs. capacity per tier. 2400 lbs. overall capacity



MS2-1532-6PH

Model No.	Openings per Level	Total Openings	OPENING SIZE			Wt.
			W	H	D	
MS1-1532-6PH	1	3	32"	12-1/2"	15"	210
MS2-1532-6PH	2	6	16"	12-1/2"	15"	217
MS3-1532-6PH	3	9	10-1/2"	12-1/2"	15"	235
MS4-1532-6PH	4	12	8"	12-1/2"	15"	252



MS1-1532-6PH



MS3-1532-6PH



MS4-1532-6PH

Stationary Storage Bins

Same heavy-duty construction as our popular Mobile Storage Bins, now in a stationary version. All welded 12 gauge steel bins with durable gray powder coated finish. The stationary versions have Fork Pockets to allow easy transport and positioning without having to empty the bins. Fork pockets with 8" x 4" opening are designed for use with either a fork truck or a standard pallet jack.

Available with 1, 2, 3, or 4 compartments per level. Overall dimensions 32" wide x 42" high x 20" deep. Shelf capacity - 800 lbs. Total Capacity - 2400 lbs.



MS3-1532-FP

Model No.	Openings per Level	Total Openings	OPENING SIZE			Wt.
			W	H	D	
MS1-1532-FP	1	3	32"	12-1/2"	15"	206
MS2-1532-FP	2	6	16"	12-1/2"	15"	213
MS3-1532-FP	3	9	10-1/2"	12-1/2"	15"	231
MS4-1532-FP	4	12	8"	12-1/2"	15"	248



MS1-1532-FP



MS2-1532-FP



MS4-1532-FP

Sloped Shelf Bin Cart

Store, organize and transport your bins (not included) with this dual-sided bin transport cart. Heavy-duty, all-welded construction. The 14 gauge solid steel shelves with 1-1/2" retaining lips are sloped at a 15° angle. The shelves are 35-1/2" wide and will accommodate bins up to 11-7/8" deep and 8" high. Shelf clearance is 8-1/4". 6 shelves on each side for a combined total of 12 shelves. 2 swivel, 2 rigid 6" non-marking polyurethane casters.

Size	Model No.	Wt.
30 x 60	6BC-3036-6PY	367



6BC-3036-6PY
Bins not included





**Model
RT4-8S**

Wire Reel Caddy

All-welded Wire Reel Caddy has four 16" wide rods for holding multiple wire reel configurations. Top 3 rods are 7" on-center. Wheels are off the ground while standing so it does not "walk" while pulling wire. Full width handle. Convenient tool tray for storage and transport of hand-tools. Heavy-duty angle iron frame. Wheels are 8" x 2-1/2" solid rubber with ball bearings. Durable powder coated gray finish. Ships via UPS!

Overall W x D x H	Model No.	Wt.
8-1/2 x 18-1/2 x 45-1/2	RT4-8S	54



**Model
RT3-12P**

Heavy-Duty Reel Caddy

1000 lbs. Capacity

Three (3) heavy-duty steel spindles are 1" diameter bar stock secured with set screws, and will accept reels up to 12" diameter and 21" wide. For larger diameter spools, simply remove 1 or more of the spindles. Large 12" diameter pneumatic wheels have roller bearings for transporting over rough surfaces. Save space, use and store vertically or horizontally. Capacity 150 lbs. per spindle. Three wire guides for dispensing. Convenient top tray measures 10" x 24". Welded unit has a powder coated finish and ships set up and ready for immediate use.

Overall W x D x H	Model No.	Wt.
36 x 31 x 45	RT3-12P	90

All-Welded Wire Reel Rack

Sturdy welded steel reel storage rack features 3 levels. The two upper levels each have three 5/8" dia. spindles, and the lower level includes a single 1" diameter spindle and two 5/8" diameter spindles. Each spindle has 33" of useable width. 150 lbs. capacity per spindle. Welded construction means no assembly. Removable wire guides. Footpads have lag holes to secure to floor. Powder coated finish.



**Model
RR-3036**

Overall W x D x H	Model No.	Wt.
36 x 30 x 72	RR-3036	178



ELECTRICIAN'S Wire Reel Cart

All-welded Electrician's Cart carries everything you need for a wiring project. Supplied with five 36" long spool holder rods for numerous wire reel configurations. Heavy 12 gauge steel shelves have a 1-1/2" lip to retain small parts. Top shelf 24" wide x 36" long x 35" high. Bottom shelf measures 24" wide x 48", providing a 12" extension for upright storage and transport of conduit or other long material. Hanger bar on side of cart for convenient ladder storage. Casters are 5" polyurethane, 2 swivel with total-lock wheel brakes and 2 rigid. Overall length is 54". Durable powder coated gray finish. Ships assembled.

Model No.	Wt.
RC2448-5PYTL	139

Wire Reel Cart with Drawers

Includes two locking storage drawers and 3 spool holder rods 36" long. Drawers have cylinder locks with 2 keys, and each measure 13" wide x 17" long x 4-1/2" high inside.

Model No.	Wt.
RC2448-5PYTL2DR	175



Model
RC2448-5PYTL



Model
RC2448-5PYTL2DR

Wire Reel Cart with Cabinet

All-welded Electrician's Cart carries everything you need for a wiring project. Supplied with five 15" long spool holder rods to allow numerous wire reel configurations. Heavy 12 gauge steel shelves have a 1-1/2" lip to retain small parts. Top shelf is 24"W x 36"L x 35"H. Storage cabinet with locking door and keyed handle measures 16"W x 23"D x 25"H. Bottom shelf measures 24"W with a 12" extension for upright storage and transport of conduit or other long material. Hanger bar on side of cart for convenient ladder storage. Casters are 5" polyurethane, 2 swivel and 2 rigid. Swivel casters feature total lock wheel brake, that locks both the swivel and the wheel. Overall length is 54". Durable powder coated gray finish.

Model No.	Wt.
RCM2448-5PYTL	152



Model
RCM2448-5PYTL

Maintenance Cart with Cabinet and Drawers

1200 lbs. Capacity

All-welded 12 gauge construction. Top work surface measures 24" x 36" and features a front flush edge and 1-1/2" retaining lips on sides and back. 4 locking storage drawers measuring 13"W x 17"L x 4-1/2"H. 27" high enclosed cabinet with locking door. 12" extension on the bottom is perfect for upright storage and transport of long material. Hanger bar on back side of cart for convenient ladder storage. 2 rigid, 2 swivel 5" non-marking polyurethane casters feature a total lock wheel brake that locks both the swivel and the wheel. Overall length is 54". Durable powder coated gray finish.

Model No.	Wt.
RCM2448-TL-4DR	236



Model
RCM2448-TL-4DR



**Double Sided
with Pegboard,
Shelves, and Tray**



**Single Sided
AFS-2440-6PH**



**DOUBLE Sided
AFS-3640-6PH**



AF-ARM
4 attachments shown

Adjustable Tray A-Frame Shelf Trucks

2000 lbs. Capacity

Use in your Lean Manufacturing facility to transport and store components or finished products where and when you need them. Slotted steel uprights accept shelves, arms, trays, and pegboard panels making this a versatile ergonomic product. Mix and match to fit your exact requirements. Since it is adjustable you can reconfigure the truck as your needs change. Available as a single sided or double sided unit. All-welded construction with a durable powder coat finish and 2 rigid and 2 swivel 6" phenolic wheels.

A-Frame	W x D x H	Model No.	Wt.
Single-sided	40 x 24 x 67	AFS-2440-6PH	72
Double-sided	40 x 36 x 67	AFS-3640-6PH	92
Double-sided w/bottom shelves	40 x 36 x 67	AFSF-3640-6PH	116

9" DEEP TRAYS are 3" high on 3 sides. Open front side available with a 1" lip, or flush edge.

15" DEEP TRAYS are 6" high on 3 sides with handles on both ends. Open front side available with 1" lip, or a flush edge.

FLUSH SHELVES have a 1-1/2" lip along the back, flush edge on 3 sides. Ideal for long and oversize items.

PEGBOARD PANELS are 16 gauge formed steel with holes on 1" centers to accept most common light and heavy-duty hooks. (Pegs and bins not included.)

ROUND TUBING ARM ATTACHMENTS (AF-ARM) are 1-1/4" OD, 8" inside length and adjustable on 3-1/2" increments. Perfect for carrying tubing and bar stock.

Tray Model No.	W x D x H	Front Edge	Max per frame		Wt.
			1-sided	2-sided	
AF-SHELF-9	36 x 9 x 3	flush	8	16	25
AF-SHELF-9-LU	36 x 9 x 3	1" lip	8	16	25
AF-SHELF-15	36 x 15 x 6	flush	5	10	33
AF-SHELF-15-LU	36 x 15 x 6	1" lip	5	10	33
AF-SHELF-FLUSH	36 x 15 x flush	flush	16	32	19
AF-PB	36 x 1 x 24	NA	2	4	17
AF-ARM*	8" inside length	-	7 pairs	14 pairs	3

* Order each individually

Adjustable Shelf Rack

Configure this rack to your exact "lean manufacturing" requirements. Standard model includes two 15" deep x 36" wide shelves that are adjustable on 3-1/2" increments. Add optional accessories to customize the rack to fit your needs. The 9-1/4" high deck surface measures 9" deep x 42" across with 1" retaining lip. All-welded construction with 2 swivel and 2 rigid 6" phenolic wheels and powder coated surface.

W x D x H	Model No.	Wt.
40 x 36 x 67	ABS-3640-6PH	154

Additional Flush Shelves

1-1/2" lip along the back, flush edge on 3 sides. Ideal for long and oversize items.

Model No.	Wt.
AF-SHELF-FLUSH	19



**Model
ABS-3640-6PH**



Mobile Pegboard A Frame – Lean Tool Cart

1200 lbs. Capacity

Use in your Lean Manufacturing facility to transport and efficiently organize tools and equipment. Visually locate tools and items in seconds. Use tool shadowing on the pegboards to know immediately if a tool, accessory, or part is missing. The 16 gauge pegboard has holes on 1” centers that accepts most common light and heavy-duty hooks. Pegboards are 48” high. Overall height is 56”. This all-welded, heavy-duty, durable unit features a durable powder coated gray finish. Ships fully assembled. 2 rigid and 2 swivel 5” polyurethane wheels make it easy to safely transport your tools to the work area. (Pegs and bins not included.)

Size	Model No.	Wt.
24 x 36	AFPB-2436-5PY	124
24 x 48	AFPB-2448-5PY	157
24 x 60	AFPB-2460-5PY	190



Model AFPB-2436-5PY

Mobile Pegboard A-Frame – 60” Tall

1200 lbs. Capacity

Efficiently organize, store and transport your tools with this Little Giant lean tool cart. 60” tall x 48” wide 16 gauge pegboard panels provide ample storage for all of your tools and feature holes on 1” centers and accept most common light and heavy-duty hooks. 5” non-marking polyurethane wheels with 2 rigid and 2 swivel casters with total lock brakes to keep the unit stationary. 68” Overall height. Available as a single or double-sided unit. (Pegs and bins not included)

A-Frame	Model No.	Wt.
Single-sided	AFPB1S2448-TL60	107
Double-sided	AFPB2S2448-TL60	163



Model AFPB2S2448-TL60

Mobile Pegboard with Back Shelf Storage

2000 lbs. Capacity

Combine the great features of our 48” high A Frame Peg Board with 4 storage shelves on the back side to store larger parts or tools. Pegboard is 16 gauge steel with 1/4” dia holes. 2 rigid and 2 swivel casters with 6” polyurethane wheels mean smooth transport through your facility. A floor lock is mounted on the swivel caster end to securely position the unit. 60” overall height.

Size	Model No.	Wt.
24 x 36	AFPBS2436-6PYFL	186
24 x 48	AFPBS2448-6PYFL	224
24 x 60	AFPBS2460-6PYFL	262



Model AFPBS2436-6PYFL



Side view