

VP Series

# Vinyl-Pro

Roll-Up Door



*Pictured: Model VP 4000*

- **Separates Environments**
- **Increases Energy Savings**
- **Blocks Dust and Airborne Pollutants**
- **Reduces Noise**
- **Improves Employee Comfort, Security and Productivity**



*Pictured: Model VP 3000*

## Modular Panels

Innovative design with interchangeable door panels makes TMI's Vinyl-Pro easily convertible to a Screen-Pro or Bird-Pro.

## Extruded Aluminum Guide Tracks

Guide the Vinyl-Pro roll-up door smoothly with UHMW<sup>‡</sup> inserts, reducing friction and adding an additional layer of protection and security.

## Extruded Aluminum Wind Bars

These high-strength stiffeners combat winds and negative air pressure.

## Save-T<sup>®</sup> Breakaway Bar

Prevents Vinyl-Pro doors from breaking if hit. The bottom bar releases in either direction and can easily be put back into the track.

<sup>‡</sup> UHMW: Ultra-High-Molecular-Weight Polyethylene

5350 Campbells Run Road Pittsburgh, PA 15205  
**1.800.888.9750** 412.787.9750 412.787.3665 (fax)  
www.tmi-pvc.com info@tmi-pvc.com



Vinyl-Pro Roll-Up Doors are available in 18 oz, 22 oz or 40 oz PVC Coated Vinyl with optional clear PVC vision panel.

Popular Vinyl-Pro Colors, Consult Factory for Additional Color Options.



**VP 1000** **Spring Loaded Manual Roll-Up Door**  
*Maximum Door Size: 10' wide x 10' high*  
The VP-1000 features a spring-loaded manual movement mechanism with pull down straps.

**VP 2000** **Chain Hoist Manual Roll-Up Door**  
*Maximum Door Size: 14' wide x 14' high*  
The VP-2000's right side mounted chain hoist is an economical alternative to motorized doors.

**VP 3000** **In-Tube Motorized Roll-Up Door**  
*Maximum Door Size: 14' wide x 14' high*  
The VP-3000's in-tube motor moves the door at a rate of 12" per second and can be cycled 8 to 10 times per hour. The VP-3000 includes an up/down constant contact rocker switch.

**VP 4000** **External Jackshaft Motorized Roll-Up Door**  
*Maximum Door Size: 14' wide x 14' high*  
The external jackshaft motor on the VP-4000 moves the door at a rate of 12" per second and can be cycled 10 to 15 times per hour. The VP-4000 includes a 3 Button Station and Photo Eye.

**VP 5000** **High-Cycle Motorized Roll-Up Door**  
*Maximum Door Size: 14' wide x 14' high*  
The VP-5000 features a heavy-duty, high-cycle, external jackshaft motor that moves the door at a rate of 12" per second. The VP-5000 includes a 3 Button Station and Photo Eye.

**VP 6000** **Swift Speed Motorized Roll-Up Door**  
*Maximum Door Size: 14' wide x 14' high*  
The VP-6000 features a heavy-duty, high-cycle, higher speed external jackshaft motor that opens the door at a rate of 30" per second. The VP-6000 includes a 3 Button Station and Photo Eye.

#### **In-Jamb**

Requires approximately 8.5" headroom and 4.5" of space on each side of the jamb

#### **Face of Wall**

Use when no existing door is present  
- can be mounted inside or outside

#### **Inside Stand-Off**

Mounts in front of an existing roll-up or sectional door

- Remote Control
- Safety Reversing Edge
- Photo Eye
- Pullcord Station

- NEMA-4 Upgrade
- Safety Reversing Edge
- Pullcord Station
- Remote Control

- NEMA-4 Upgrade
- Safety Reversing Edge
- Pullcord Station
- Remote Control
- Motion Sensors

- NEMA-4 Upgrade
- Safety Reversing Edge
- Pullcord Station
- Remote Control
- Motion Sensors

**For Energy Control and Workplace Safety Call TMI at 1.800.888.9750 Today!**



5350 Campbells Run Road Pittsburgh, PA 15205  
**1.800.888.9750** 412.787.9750 412.787.3665 (fax)  
www.tmi-pvc.com info@tmi-pvc.com

Catalog #  
P1-6000 052013 R01